

(12) United States Patent Suzuki

(10) Patent No.:

US 6,318,171 B1

(45) Date of Patent:

Nov. 20, 2001

(54) FLOW RATE SENSOR IMPLEMENTING A PLURALITY OF INNER TUBES LOCATED WITHIN A SENSOR TUBE

(75) Inventor: Isao Suzuki, Tokyo (JP)

(73) Assignee: MKS Japan, Inc., Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/451,927

(22) Filed: Dec. 1, 1999

(30) Foreign Application Priority Data

Dec Jun.	c. 1, 1998 18, 1999	(JP) (JP)	• • • • •	 	••••••				10-34 11-17	41800 72854
(51)	Int. Cl. ⁷			 				. G	01F	1/68
(52)	U.S. Cl.		• • • •	 				7	73/20	04.27
(58)	Field of	Search		 		. 7:	3/204	4.22	2, 20	4.27,
								7	73/20	04.15

(56) References Cited

U.S. PATENT DOCUMENTS

5,410,912	•	5/1995	Suzuki	73/204.22
5,741,968	*	4/1998	Arai	73/204.22
5,792,952	*	8/1998	Ritchart	73/204.27
6,125,695	*	10/2000	Alvesteffer et al	73/204.27

* cited by examiner

Primary Examiner—Harshad Patel

(74) Attorney, Agent, or Firm-Wenderoth, Lind, and

Ponack, L.L.P.

(57) ABSTRACT

There is provided a flow rate sensor comprising: a pair of heating resistors operable to heat a sensor tube; a temperature sensor operable to control respective temperatures of the heating resistors; and a case operable to hold the heating resistors and the temperature sensor. The flow rate sensor is adapted to detect a flow rate of a fluid flowing in the sensor tube based on variations of voltages applied to the heating resistors, wherein the variations occur according to the flow rate of the fluid. The flow rate sensor further comprises a voltage applying device operable to arbitrarily set an increase in temperature of each of the heating resistors. The sensor tube has opposite ends thereof thermally connected to the case. The temperature sensor is positioned to be equidistant from the opposite ends of the sensor.

8 Claims, 11 Drawing Sheets



